

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 August 2002 (29.08.2002)

PCT

(10) International Publication Number
WO 02/065858 A1

(51) International Patent Classification⁷: A23L 1/22,
A61K 7/00, 7/46, 9/16, A23P 1/02, 1/04, C11D 3/50, 9/44

(74) Agent: SALVATERRA-GARCIA, Maria de Lurdes;
FIRMENICH SA, P.O. Box 239, CH-1211 GENEVA 8
(CH).

(21) International Application Number: PCT/IB02/00404

(22) International Filing Date: 8 February 2002 (08.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/784,121 16 February 2001 (16.02.2001) US

(71) Applicant (for all designated States except US): FIR-
MENICH SA [CH/CH]; 1, route des Jeunes, P.O. Box
239, CH-1211 Geneva 8 (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MCIVER, Robert,
C. [US/US]; 15 Lillian Street, Tabernacle, NJ 08088
(US). VLAD, Florin [CA/US]; 9 Kent Court, Annandale,
NJ 08801 (US). GOLDING, Robert, A. Jr. [US/US];
2204 Quail Ridge Drive, Plainsboro, NJ 08536 (US).
LEICHSENRING, Travis, D. [US/US]; 297 Ewingville
Road, Ewing, NJ 08638 (US). BENCZEDI, Daniel
[CH/CH]; 17 rue du Grand-Bureau, CH-1227 Carouge
(CH).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



WO 02/065858 A1

(54) Title: ENCAPSULATED FLAVOR AND/OR FRAGRANCE COMPOSITION

(57) Abstract: The invention relates to a granular delivery system based on a matrix combining at least a carbohydrate material with from 1 to 7% of prehydrated agar agar. The system disclosed is particularly stable in aqueous environments and is capable of providing the controlled release of an active flavoring or perfuming ingredient there-encapsulated.

Encapsulated flavor and/or fragrance composition**Technical field**

5

The present invention relates to the flavor and fragrance industry. It concerns more particularly an encapsulated system consisting of an extruded product, particularly stable in an aqueous environment and which is capable of releasing a flavoring or perfuming ingredient or composition in a controlled manner, under specific conditions
10 such as for instance shear force or heat.

Background of the Invention

15

Encapsulated systems represent an important technology for the flavor and fragrance industry.

Encapsulated systems are designed so as to achieve two kinds of objectives. The first goal typically sought is related to the function of protection of the ingredients covered by such systems. In fact, these systems must be capable of protecting an active
20 material there-encapsulated from different types of "aggressions" such as oxidation or moisture. The stabilization of these systems constitutes therefore a critical issue in the field.

Another objective always targeted for an encapsulated system consists in controlling in an appropriate way (depending on the final application) the release of the
25 active ingredient or composition encapsulated. In particular, in the case where the active ingredient is volatile, it may be of much importance to sustain and control its release during a prolonged period of time.

The complexity of such systems, as well as the variety of applications there-related, justify a constant need to improve encapsulated systems and processes for making
30 them so as to obtain products which satisfy all the requirements needed, such as a good stability under certain use conditions or an optimized controlled release of the encapsulate.

The prior art and in particular the patent literature describes a large number of encapsulated systems prepared by way of extrusion methods. Extrusion methods typically rely on the use of carbohydrate matrix materials which are heated to a molten state and

combined with an active ingredient, before extruding and quenching the extruded mass to form a glass which protects said ingredient. Typical products issued from these methods and used in the flavor industry are dry, granular delivery systems in which the active ingredient is a flavor uniformly distributed as droplets throughout a carbohydrate glass.

5 One significant example of the prior art disclosure in this field is US 3,704,137 which describes an essential oil composition formed by mixing an oil with an antioxidant, separately mixing water, sucrose and hydrolysed cereal solids with DE below 20, emulsifying the two mixtures together, extruding the resulting mixture in the form of rods into a solvent, removing the excess solvent and finally adding an anti-caking agent.

10 Another pertinent example is that described in US 4,610,890 and US 4,707,367 which disclose a process for forming a stable, melt based and extruded, solid, essential oil flavor composition, as well as a product of this process. The melt to be extruded consists, in this particular case, in a matrix formed of an aqueous mixture of a sugar and a starch hydrolysate together with a selected emulsifier, said aqueous mixture being further blended
15 with a selected quantity of essential oil flavor. The above-mentioned patents, and all the other prior art there-cited, are merely illustrative of the considerable volume of patent literature related to the fixation of flavor ingredients in various matrices and which, in essence, discloses the encapsulation of flavor materials in glass-like polymeric materials, in particular carbohydrate matrices.

20 A large variety of matrix components are disclosed in this prior art and play a part in the release process of these systems. In the case of systems based on the use of carbohydrate materials, said carbohydrates dissolve almost instantly in the presence of water, thus releasing the flavor into the aqueous environment. Complete dissolution and flavor liberation occur in less than 1 minute and may last up to 2 minutes, depending on the
25 exact composition of the matrix.

 Now, in applications where water is present, a better retention of a flavor within a particle may be needed. Similarly, the field of perfumery embraces many applications where a prolonged diffusion of the perfuming ingredients or compositions through particles which encapsulate them may be desired.

30 Some methods to achieve those effects are known and generally consist in making particles with an insoluble surface (coacervation, coating with a fat). However, said techniques require an additional step (coating) and do not provide optimal results.

 Now, the present invention offers a product with a retarded flavor or fragrance release in water, and which is an improvement of standard extrusion technology such as

disclosed in the above-mentioned patent literature as well as in other documents cited below. In fact, we have now been able to realize a novel granular i.e. extruded system capable of controlling the release of an active ingredient, in particular in an aqueous environment. Said system is based on the use of agar agar in its matrix composition.

5 Amongst the large number of materials disclosed in the prior art as being potentially useful in matrix compositions of encapsulated systems, agar agar is often cited and used either as a coating material, or as a binder or granulating agent.

 Agar agar is part of the family of hydrocolloids, also referred as gums. Hydrocolloids are long-chain high molecular weight polymers that disperse and hydrate in
10 water to give a thickening and sometimes a gelling effect.

 A large amount of the patent literature related to encapsulated systems cites agar agar as part of the possible encapsulation materials. For instance, WO 99/27798, which describes improved chewing gum formulations including sodium bicarbonate and Aspartame® in an encapsulated form, discloses agar agar in a list of coating ingredients,
15 said list also comprising in particular dextrin, modified starch, acacia or maltodextrin. On the other hand, agar agar is also cited in some documents as being used as a granulating agent. In particular, US 4,911,934, which also describes a chewing gum composition including encapsulated sweeteners and having an extended flavor release, discloses the use of agar agar as a granulating agent, capable of causing agglomeration or aggregation of the
20 sweetening agent particles.

 Therefore, agar agar has a widespread use in foods as stabilizer, thickener, humectant and surface finisher. Like many other colloids, agar agar also has film forming and bioadhesive properties. However, although other hydrocolloids are frequently cited in specific examples of the patent literature, agar agar only appears as part of the all
25 encompassing list of gums, hydrocolloids, film forming agents and bioadhesives and is disclosed generally as a possible useful material, but not specifically exemplified.

 Yet, we have now been able to establish that, in combination with a carbohydrate material and when used in far smaller amounts than those disclosed in the prior art, agar agar is a very useful matrix material and provides particularly advantageous
30 effects on extruded systems, stabilising them in an aqueous environment and improving the retention of the active ingredient or composition there-encapsulated.

Brief Summary of the Invention

The present invention thus relates to a granular delivery system comprising a flavor or fragrance ingredient or composition distributed as droplets throughout a matrix of polymeric carriers, wherein said carriers comprise at least a carbohydrate material and from 1 to 7% of prehydrated agar agar, based on the dried weight of the granular system, i.e. of the extruded product.

The system of the present invention presents many advantages. In particular, the incorporation of agar agar in such specific proportions advantageously prevents the release of the flavor or fragrance ingredient or composition, hereafter referred to as the "active" ingredient in an aqueous environment. In fact, in the presence of water, the delivery system of the invention, in the form of particles, rehydrates and rapidly forms an agar agar-carbohydrate gel structure which physically traps the active ingredient, usually in the form of oil droplets. In the case where a flavor ingredient is encapsulated, the system of the present invention allows the retention of the flavor within the particles in applications where water is present, until shear or heat are applied to cause release of the active ingredient. The system is thus very advantageous in applications such as chewing gums and soft chewy confections or ice creams for instance. In particular, chewy sweets constitute the most typical example in which the carrier is expected to release the active ingredient only upon chewing, thus providing flavor hot spots and further avoiding an early exposure of the flavor to the fats contained in these products.

In the case of fragrances, the diffusion of the active ingredient from the particles may take several hours depending on the external environment and the invention thus provides an interesting controlled release system, in applications related to functional perfumery.

On the other hand, the composition of the matrix according to the present invention is adapted, from a process point of view, to be extruded according to usual techniques. By "usual extrusion techniques", we mean here methods according to which, typically, an aqueous carbohydrate melt, the active material and an optional emulsifier are allowed to form an homogeneous emulsion, which is extruded under pressure through a die plate and then cooled to form a solid product containing the active material, dispersed as fine droplets.

A large number of particular embodiments of this general method are described in the varied patent literature related to extrusion techniques and may be used for

processing a matrix according to the invention. Some of these processes will be described in a more detailed manner below.

The active materials advantageously encapsulated according to the invention can be selected among all the current flavor and fragrance materials, which are preferably hydrophobic. Hydrophilic components may also be used, but their release may be less retarded as a function of their partition in the outer aqueous environment. The examples given hereafter are meant to illustrate a variety of embodiments of the invention but are not to be interpreted as limiting the latter.

More objects, aspects and advantages of the invention will become apparent from the detailed description hereafter.

Detailed Description of the Invention

It has been unexpectedly discovered that agar agar can be advantageously used in very small amounts, in combination with a carbohydrate material, in the composition of the matrix of an extruded system, said system being consequently stable for a prolonged period in water, and releasing in a controlled manner the active ingredient there-encapsulated.

As previously cited, one object of the present invention is to provide a granular delivery system comprising a flavor or fragrance ingredient or composition dispersed as droplets throughout a matrix of polymeric carriers, wherein said carriers comprise at least a carbohydrate material and from 1 to 7% of agar agar. The percentage of agar agar as well as all the proportions mentioned below are given by weight relative to the dried weight of the extruded product. The agar agar used in the invention is in a prehydrated form.

The system of the invention is particularly advantageous when used in an aqueous environment. In fact, the specific combination of a carbohydrate material with agar agar in the above-cited range of concentrations unexpectedly allows the formation of a gel barrier which prevents the granules from an immediate dissolution in water as it was the case in the prior art, thus providing a slow release of the flavor or fragrance droplets. The invention advantageously provides a system showing a high percentage of retention of the active ingredient there-encapsulated after the particle rehydration, while being easy to manufacture with standard manufacturing equipment.

It is particularly surprising to observe the effectiveness of agar agar at such a low concentration and at the same time its advantages from a process point of view, as heretofore, in extrusion processes for example, the viscosity constitutes a limiting factor of the amount of gum that can be incorporated. The range of concentration of agar agar is
5 totally unexpected and represents an essential characteristic of the invention.

The matrix of the delivery system according to the present invention comprises at least the above-mentioned combination, namely a carbohydrate material and from 1 to 7% of agar agar. Preferably it contains from 1 to 3% and more preferably from 1 to 1.5% of agar agar. The proportions of carbohydrate material are usually comprised between 0
10 and 95% relative to the dried extruded product, and preferably between 40 and 90%.

As the carbohydrate material used in combination with agar agar in the delivery system of the invention, there can be used any sugar or sugar derivative which can be readily processed through extrusion techniques to form a dry extruded solid. Particular examples of suitable materials include those selected from the group consisting of sucrose,
15 glucose, lactose, levulose, fructose, maltose, ribose, dextrose, isomalt, sorbitol, mannitol, xylitol, lactitol, maltitol, pentitol, arabinose, pentose, xylose, galactose, hydrogenated starch hydrolysate or succinylated, chemically modified starch, corn syrup, maltodextrin, polydextrose and derivatives and mixtures thereof.

In one particular embodiment of the invention, the carbohydrate material is
20 selected from the group consisting of maltodextrin or a corn syrup, a chemically modified starch, a hydrogenated starch hydrolysate or a succinylated or hydrolyzed starch. Preferably, the maltodextrin used has a dextrose equivalent (DE) of at least 18.

Following specific embodiments, there will be used polymeric carriers which include maltodextrin. The latter can be the main carbohydrate material of the matrix, or
25 yet, be used in admixture with any one of the sugars mentioned above, preferably sucrose.

In another embodiment, the polymeric carrier consists of maltodextrin in the form of a narrow cut of polymer chains (Glucidex® C1872 ; origin : Roquette America, Inc. Keokuk, Iowa, USA) and from 1 to 7% of agar agar.

The active ingredient encapsulated in the system according to the invention
30 will preferably be a hydrophobic flavor or fragrance ingredient or composition of current use. However the polarity or aqueous solubility of the active ingredient may be chosen as a function of the desired retardation of the release for a given application. In fact more hydrophilic components will be released faster as they are able to partition in the outer aqueous environment.

The terms flavor or fragrance ingredient or composition as used herein are deemed to define a variety of flavor and fragrance materials of both natural and synthetic origin. They include single compounds and mixtures. The system of the invention may encapsulate volatile or labile components which may be in liquid or solid form, preferably hydrophobic. Specific examples of such components may be found in the current literature, e.g. in Perfume and Flavour Chemicals by S. Arctander, 1969, Montclair N.J. (USA); Fenaroli's Handbook of Flavour Ingredients, 1975, CRC Press or Synthetic Food Adjuncts, 1947, by M.B. Jacobs, van Nostrand Co., Inc. and are well-known to the person skilled in the art of perfuming, flavoring and/or aromatizing consumer products, i.e. of imparting an odor and/or a flavor or taste to a consumer product traditionally perfumed or flavored, or of modifying the odor and/or taste of said consumer products.

Natural extracts can also be encapsulated into the system of the invention; these include e.g. citrus extracts such as lemon, orange, lime, grapefruit or mandarin oils, or coffee, tea, cocoa, mint, vanilla or essential oils of herbs and spices, amongst other.

The proportion of active ingredient in the matrix is comprised between 0.1 and 25% by weight relative to the dried extruded product, and preferably between 5 and 16%.

Apart from flavor and fragrance ingredients or compositions, the system of the present invention can suit the encapsulation of other active ingredients that one wishes to encapsulate such as pharmaceuticals for instance.

An emulsifier agent may be added to the mixture constituted by the matrix components and the active ingredient, in proportions varying typically from 0.1 to 10%, and preferably from 0.4 to 2%, relative to the solid product. Typical examples include soya lecithin and citric acid esters of fatty acids, but other suitable emulsifiers are cited in reference texts such as Food Emulsifiers and Their Applications, 1997, edited by G.L. Hasenhuettl and R.W. Hartel, USA.

Other additional ingredients of current use in the art of extruded products may be added to the matrix such as free flow agents, or coloring materials, both natural or artificial.

Typically, the final products have a moisture content comprised between 2 and 8%.

The system of the present invention shows an unexpected and advantageous behavior in an aqueous environment, which can be displayed during a rehydration process. In fact, while a classical encapsulation system such as disclosed in the prior art, represented for example by US 4,610,890 or US 4,707,367, would dissolve instantly or

rapidly in water, thus releasing immediately the active ingredient oil droplets, the granules according to the invention, due to the formation of a more or less strong gel, prevent the instant release of the oil. During a rehydration process, a gel layer is rapidly formed at the surface of the product. Once the initial layer is formed, no loss of flavor or fragrance oil droplets can occur into the surrounding water. There does not appear to be coalescence of the oil droplets. After complete rehydration in typically 4 to 5 min., the particle is a flexible gel. Strong pressure applied to the particle results in the breakage into smaller gelled pieces. Flavor or fragrance oil is released at the fracture point only.

Another object of the present invention is a process for the preparation of a delivery system as defined above, comprising the basic steps of

- a) combining and blending a flavor or fragrance ingredient or composition with a matrix comprising an aqueous solution of at least a carbohydrate material, from 1 to 7% of prehydrated agar agar and optionally an emulsifier, under temperature and stirring conditions useful to produce a uniform melt thereof ;
- b) extruding the uniform melt through a die ;
- c) chopping, cutting, grinding or pulverising the material obtained as it exits the die or after cooling the melt ; and
- d) optionally drying.

In the process of the invention, agar agar is used in a prehydrated form.

The process above-described embraces a variety of extrusion techniques, depending notably on the materials used and on the amount of water added in the first step of the process, which may have to be reduced during a drying step in order to obtain a final product having an acceptable glass transition temperature (T_g). In fact, the critical glass transition temperature may be at least above 20°C and preferably above 40°C for the major part of applications. However in some cases, it may be useful to prepare delivery systems which have glass transition temperatures below ambient temperature as disclosed in WO 96/11589, the content of which is hereby included by reference. The proportions in which water is employed in the present invention therefore vary in a wide range of values which the skilled person is capable of adjusting and choosing as a function of the carbohydrate glass used in the matrix and the required T_g of the final product.

According to one particular embodiment, typical conditions for this process are similar to those described for example in US 3,704,137, the contents of which is hereby included by reference. More particularly, in step a), the carbohydrate material is mixed with a sufficient amount of water and heated to form a solution. Separately, the agar agar is

mixed with approximately 11 times its weight in water and allowed to rehydrate. The agar agar suspension is then added to the carbohydrate solution which is then heated to remove sufficient water to form a viscous melt containing from 3 to 12% of water. The active ingredient and an optional emulsifier are then mixed with the melt under high shear to
5 uniformly disperse the active ingredient throughout the melt. In another embodiment, the agar agar suspension is added to the preformed emulsion consisting of the active ingredient dispersed as droplets in the carbohydrate matrix. This is then extruded under pressure through a die plate (step b)) and falls into a chilled solvent where the material is cooled to a glass, chopped and the surface washed of actives (step c)). The particles are then dried to
10 remove residual solvent and reduce the moisture content to from 2 to 8%. The shape and size of the extruded solid can be adjusted as a function of the extrusion parameters. The temperature and pressure conditions under which this process is carried out are current and fully described in the US document cited above, the teaching of which is hereby included by reference and forms an integral part of the present specification. Such parameters can
15 therefore be adjusted by the skilled person without particular effort and as a function of the nature of the ingredients present in the melt and of the quality of the product which is desired to obtain, i.e. its granulometry and shape. The type and design of the equipment used require no detailed description here, the expert in this field being well-acquainted with current apparatuses, their technical specificities and the choice of appropriate
20 equipment for a desired specific shape and size of the extruded solid. It is well-known, moreover, that such extruded solids may be produced in many forms, i.e. powders of varied granulometry, rods, flakes, filaments, etc. Techniques such as grinding (or criogrinding), pulverising or sieving are also known to further provide for reduction of the size of the extruded solid, namely in the case of extruded particulate solids, to reduce it to
25 the state of fine micromized powders, if so desired.

Another kind of extrusion technique suitable according to the present invention, namely wet-granulation, is described in EP 202409, the content of which is included herewith by reference. This method also comprises step d) of the above-mentioned process, namely a drying step. More particularly, this document discloses a
30 method for the production of stable, spherical particles of viable micro-organisms which comprises the steps of mixing a culture concentrate with a bulking agent to form a homogeneous wet granulate, extruding the wet granulate through a die to produce filaments having a diameter of approximately the size of the desired spheres and then using a spheroniser device which comprises a plate that rotates at a tangential speed sufficient to

cause the filaments to be shaped into discrete spherical particles, and finally drying the particles. Before the drying step, the glass transition temperature of the extruded mass is relatively low because of the large proportion of water used as plasticiser. The additional drying step is thus necessary to evaporate some water from the system, thus increasing the Tg to a sufficient value to provide a product capable of being stored at room temperature.

According to another extrusion method suitable for the instant invention, the drying step may be avoided. In that case, there is no need to first blend the hydrophilic active material and the matrix materials with a large amount of water to obtain a homogeneous melt. It is possible in fact to heat a substantially solid mixture of these ingredients, containing only a small amount of plasticiser, to its glass transition temperature, and to press-feed the extruder with this substantially solid mass, under efficient mixing, to ensure formation of an homogeneous melt and obtain a stable extruded product. The so-called "dry-blend" extrusion techniques obey this principle, and they typically require the use of higher pressures to feed the melt of the originally essentially solid material through the extruder than the methods cited above which resort to the extrusion of substantially liquid or fluid mixtures of ingredients.

Thus, in the processes described in the above-mentioned literature and in the prior art in general, which are adapted to the present invention, the homogeneous mixture of active ingredient and carbohydrate matrix prepared in the first step of the process is heated within a screw-extruder in such a way that the temperature of the mixture is above the glass transition temperature of the matrix in order to form a molten mass. Then, the molten mass is extruded through a die.

Step c) of the process depends on the technique used. In the first technique described here-above (notably disclosed in US 3,704,137), the molten mass can be cooled as it exits the die to a temperature below the glass transition temperature of the matrix. Extruded granules can be manufactured by breaking the extruded material cooled below its glass transition temperature. This crushing step unavoidably loses a certain amount of matter because of the hardness of the material and it can also happen that the encapsulated volatile compound is damaged and partially lost during this step.

In other cases, wet-granulation or melt granulation is used to chop the extruded product as it is still in a plastic state above its glass transition temperature.

According to the last extrusion technique above-described, wherein the matrix contains a small amount of water, there are provided solid delivery systems which are prepared via a process according to which the uniform melt produced in step a) is obtained

by heating the mixture of matrix carbohydrate material, agar agar and active ingredient to a temperature comprised between 90 and 130°C, the mixture being then subsequently extruded through a die and the molten mass being chopped as it exits the die and before it is cooled to solidify.

5 According to this particular embodiment, a low water content is added to the mixture to be melt to guarantee that the glass transition temperature T_g of the resulting melt corresponds to, and is substantially the same as, that of the desired T_g value of the final product. In other words, contrary to other methods such as wet-granulation, the glass transition temperature of the mixture before extrusion has already the value required for
10 the final product, which temperature is above 20°C and preferably above 40°C so that the product can be stored at ambient temperature in the form of free-flowing granules. As a consequence, this embodiment of the invention can dispense with the additional drying step following the extrusion, intended to remove water in order to increase T_g to an acceptable value. Moreover, the extruding step of this process requires an extruding
15 apparatus. A commercially acceptable extruding apparatus is that under the trade name designation of Clextral BC 21 twin-screw extruder equipped with a cutterknife allowing to chop the melt at the die exit, when it is still plastic. However, extruding apparatuses are not limited to the twin screw variety and may also include, for example, single screw, ram, or other similar extrusion methods. The extrusion apparatus is equipped with a temperature
20 regulation mechanism allowing to increase progressively the temperature of the mixture up to a value comprised typically between 90 and 130°C, at which point it can be extruded through a die.

The instant extruded solids resulting from any embodiment of the process according to the invention can be advantageously used to impart or modify the
25 organoleptic properties of a great variety of edible or perfumed end products. In the field of flavors, these consumer products may include foods, beverages, pharmaceuticals and the like. The incorporation of granules according to the invention in chewing gums or soft chewy confections, tooth-pastes and ice-creams is straightforward and provides improved effects. On the other hand, in the field of perfumery, the granular solids according to the
30 invention may be advantageously incorporated in a perfuming composition added to functional products such as soaps, bath or shower gels, deodorants, body lotions, cosmetic preparations, shampoos or other hair-care products, cleaning products. These examples are of course not exhaustive and are not restrictive of the invention.

The concentrations in which the extruded solids can be incorporated in such consumer products vary in a wide range of values, which are dependent on the nature of the product to be flavored or perfumed. Typical concentrations, to be taken strictly by way of example, are comprised in a range of values as wide as from a few ppm up to 5 or even 10% of the weight of the flavoring or perfuming composition or finished consumer product into which they are included.

Adjuvants such as for example food grade colorants can also be added in a generally known manner, to the extrudable mixtures of the invention, so as to provide colored flavor or perfume systems and granulates.

The invention will now be illustrated by way of the following examples but is not limited to these examples. Temperatures are given in degrees centigrade and abbreviations have the meaning common in the art.

Embodiments of the Invention

Example 1

Preparation of a granular delivery system according to the invention

A matrix formulation was prepared with the following ingredients

	<u>Ingredients</u>	<u>Grams</u>	<u>% dry</u>
	Maltodextrin 18 DE	1300	41.50
25	Sucrose	1300	41.50
	Cinnamic aldehyde	470	15.00
	Agar agar ¹⁾	31	1.0
	Soya lecithin ²⁾	31	1.0
	Water	800	-----
30	Total		100.00

1) origin : TIC Gums Inc., Belcamp, Maryland, USA

2) origin : Central Soya, Fort Wayne, Indiana, USA

The agar agar was mixed with 400 g of water to form a slurry. This was added to a syrup made from the sucrose, maltodextrin and 400 g of water. The mixture was heated to 123° to reduce the moisture content of the syrup. The cinnamic aldehyde and emulsifier were mixed with the concentrated syrup with high shear to form a uniform melt which was then
 5 extruded under 2×10^5 Pa pressure through a die plate with 0.8 mm diameter holes into a cold solvent for chilling and breaking of the strands. After drying, 0.5% silicon dioxide was added as free flow agent. The resulting product contained 13.6% by weight of cinnamic aldehyde, 5.7% moisture and had a glass transition temperature of 34°.

When 50 g of particles were placed in 500 ml of water, the particles swelled to
 10 approximately 3 times their original volume. After 4 days in water, the soft gelled particles were found to contain 13.1% cinnamic aldehyde by weight (based on the original dry weight of the particles).

Example 2

15

Preparation of a granular delivery system according to the invention

A matrix formulation was prepared by admixing the following ingredients

20	<u>Ingredients</u>	<u>Grams</u>	<u>% dry</u>
	18 DE maltodextrin syrup ¹⁾	4459	81.50
	Fragrance ²⁾	630	16.00
	Soya lecithin ³⁾	39	1.00
	Agar agar ⁴⁾	59	1.50
25	Water	400	-----
	Total		100.00

1) Glucidex®C 1872, 72% solids ; origin : Roquette America, Inc., Keokuk, Iowa, USA

2) origin : Firmenich SA, Geneva, Switzerland

30 3) origin : Central Soya, Fort Wayne, Indiana, USA

4) origin : TIC Gums Inc., Belcamp, Maryland, USA

The agar agar was mixed with 400 g of water to form a slurry which was then mixed into the maltodextrin syrup. Further processing steps were the same as described in Example 1.

The final granules were found to contain 14.5% fragrance, 6.3% moisture and have a glass transition temperature of 66°.

When 50 g of the particles were placed in 500 ml of water, the particles swelled to approximately 2 times their original volume. After 5 days in water, the soft gelled particles
5 were found to contain 14.1% fragrance by weight (based on the original dry weight of the particles).

Example 3

10 Preparation of a granular delivery system according to the invention

A matrix formulation was prepared by admixing the following ingredients

	<u>Ingredients</u>	<u>Grams</u>	<u>% dry</u>
15	Hydrogenated Starch Hydrolysate ¹⁾	4278	88.00
	Cold pressed Valencia orange oil	350	10.00
	Soya lecithin ²⁾	18	0.50
	Agar agar ³⁾	53	1.50
	Water	350	-----
20	Total		100.00

1) Polysorb[®] C 1895 68% solids ; origin : Roquette America, Inc., Keokuk, Iowa, USA

2) see Example 1

3) origin : TIC Gums Inc., Belcamp, Maryland, USA

25

The particles were prepared according to the method described in Example 2. The final product contained 9.7% of orange oil on a weight basis and 7.5% moisture.

When 50 grams of the particles were placed in 500 ml of water, the particles swelled to approximately 1.5 times their original volume. After 5 days in water, the soft gelled
30 particles were found to contain 9.1% orange oil by weight (based on the original dry weight of the particles).

Example 4Preparation of a granular delivery system according to the invention

5 A matrix formulation was prepared by admixing the following ingredients

	<u>Ingredients</u>	<u>Grams</u>	<u>% dry</u>
	18 DE maltodextrin	1505	43.00
	Sucrose	1505	43.00
10	Menthol crystals	438	12.50
	Soya lecithin ¹⁾	18	0.50
	Agar agar ²⁾	35	1.00
	Water	800	-----
	Total		100.00

15

1) origin : Central Soya, Fort Waynes, Indiana, USA

2) origin : TIC Gums Inc., Belcamp, Maryland, USA

20 The particles were prepared according to the method described in Example 1. The final product contained 10.5% menthol on a weight basis and 5.4% moisture.

When 50 grams of the particles were placed in 500 ml of water, the particles swelled to approximately 3 times their original volume.

25 For all the systems prepared under Examples 1 to 4, moisture determination of finished products was done by Karl Fisher titration. Flavor content of products was assayed by steam distillation or gas chromatography. Flavor retention after 5 days in water was determined by rehydrating 50 g of granules sized 250-850 μm in 500 ml of water in water in a shallow covered dish. After 5 days in water, the gel particles were filtered on a 250 μm mesh screen and washed with 200 ml of water. Both the washed particles and filtrate were
30 steam distillation for oil content.

The rehydration properties of the particles were examined by light microscopy.

The gelled particles appear to be stable over time as indicated by the fact that over 90% of the oil in the particles remained after sitting for 5 days in water.

Example 5Comparative example on a rehydration test

5

Four batches were prepared according to respectively Example 1, 2, 3 and 4, hereafter respectively referred as B1, B2, B3 and B4. For comparison, a fifth batch lacking agar agar was prepared according to the process described in Example 1, by admixing the following ingredients :

10

	<u>Ingredients</u>	<u>Grams</u>	<u>% dry</u>
	Maltodextrin 18 DE	1505	44.55
	Sucrose	1505	44.55
	Cold pressed Valencia orange oil	350	10.36
15	Soya lecithin ¹⁾	18	0.54
	Water	400	-----
	Total		100.00

1) origin : Central Soya, Fort Wayne, Indiana, USA

20

Moisture determination of the finished products was carried out by Karl Fisher titration. Flavor content of the products was assayed by steam distillation or gas chromatography. Flavor retention after 5 days in water was determined by rehydrating 50 g of granules sized 250-850 μm in 500 ml of water in a shallow cover dish. After 5 days in water, the

25 gel particles were filtered on a 250 μm mesh screen and washed with 200 ml of water. Both the washed particles and filtrate were steam distilled for oil content. The rehydration properties of the particles were examined by light microscopy.

Table I reports the results of these measurements :

30

Table I

Batch Number	<i>Percentage of oil retention after 5 days in water</i>	<i>Rehydration observations</i>
B1	96.3	<ul style="list-style-type: none">• Swells to 3 times volume• Soft gel formed
B2	97.2	<ul style="list-style-type: none">• Swells to 2 times volume• Soft gel formed
B3	93.8	<ul style="list-style-type: none">• Swells to 1.5 times volume• Soft gel formed
B4	92.2	<ul style="list-style-type: none">• Swells to 3 times volume• Soft gel formed
B5	0	<ul style="list-style-type: none">• Dissolution in 60 s in water• No gel formed

Claims

1. A granular delivery system comprising a flavor or fragrance ingredient or
5 composition distributed as droplets throughout a matrix of polymeric carriers, wherein said
carriers comprise at least a carbohydrate material and from 1 to 7% of prehydrated agar
agar, relative to the dried weight of the granular system.

2. A delivery system according to claim 1, wherein the carriers comprise from 1
10 to 3% of agar agar.

3. A delivery system according to claim 1, wherein the carriers comprise from 1
to 1.5% of agar agar.

4. A delivery system according to claim 1, wherein the flavor or fragrance
15 ingredient or composition is hydrophobic.

5. A delivery system according to claim 1, wherein the carbohydrate material is
selected from the group consisting of a maltodextrin or corn syrup, a chemically modified
20 starch, a hydrogenated starch hydrolysate and a succinylated or hydrolysed starch.

6. A delivery system according to claim 1, wherein the carriers consist of
maltodextrin in the form of a narrow cut of polymer chains and from 1 to 7% of agar agar.

7. A delivery system according to claim 6, wherein the carriers consist of
25 maltodextrin in the form of a narrow cut of polymer chains and from 1 to 3% of agar agar.

8. A delivery system according to claim 5, wherein the polymeric carriers further
comprise a sugar, selected from the group consisting of sucrose, glucose, lactose, maltose,
30 fructose, isomalt, sorbitol, mannitol, xylitol, lactitol, maltitol, and hydrogenated corn
syrup.

9. A delivery system according to claim 5, wherein the maltodextrin has a
dextrose equivalent equal to or above 18.

10. A delivery system according to claim 1, wherein the flavor or fragrance ingredient or composition represents from 0.1 to 25% by weight relative to the dried granular system.

5

11. A delivery system according to claim 10, wherein the flavor or fragrance ingredient or composition represents from 5 to 16% by weight relative to the dried granular system.

10 12. Process for the preparation of a delivery system as defined in claim 1, comprising the following steps :

- a) combining and blending a flavor or fragrance ingredient or composition with a matrix comprising an aqueous solution of at least a carbohydrate material, from 1 to 7% of prehydrated agar agar, and optionally an emulsifier, under temperature and stirring
- 15 conditions useful to produce a uniform melt thereof ;
- b) extruding the uniform melt through a die ;
- c) chopping, cutting, grinding or pulverising the material obtained as it exits the die or after cooling the melt ; and
- d) optionally drying.

20

13. Process according to claim 12, wherein the matrix consists of a hot carbohydrate melt of 3 to 12% moisture.

14. Process according to claim 12, wherein step d) is followed by the mixing of the
25 obtained particles with a free flow agent.

15. Use of a delivery system according to claim 1, for the release of a flavoring or perfuming ingredient or composition.

30 16. Flavored product or composition which comprises as an active ingredient, a delivery system according to claim 1.

17. Flavored product or composition according to claim 16, in the form of a chewing gum or a soft chewy confection, an ice-cream, a biscuit, a pharmaceutical preparation or a tooth-paste.

5 18. Perfumed product or composition which comprises as an active ingredient, a delivery system according to claim 1.

10 19. Perfumed product or composition according to claim 18, in the form of a soap, a shower or bath gel, a shampoo or another hair-care product, a body lotion, a cosmetic preparation, a deodorant and a cleaning product.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IB 02/00404

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23L1/22 A61K7/00 A61K7/46 A61K9/16 A23P1/02
 A23P1/04 C11D3/50 C11D9/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23L A61K C11D A23P

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, FSTA, BIOSIS, MEDLINE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 94 06308 A (MCCORMICK & CO INC) 31 March 1994 (1994-03-31) claims 1-4,7; examples; table 1 ---	1-19
A	WO 85 03414 A (SCM CORP) 15 August 1985 (1985-08-15) page 5, line 33 -page 6, line 9; claims 12-15; examples ---	1-19
A	GB 655 592 A (MIJ TOT EXPLOITATIE DER OLIEFA) 25 July 1951 (1951-07-25) example 1 ---	1-19
A	WO 00 36931 A (UHLEMANN JENS ;BOECK REINHARD (DE); HAARMANN & REIMER GMBH (DE); H) 29 June 2000 (2000-06-29) example 9 ---	1-19
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
 E earlier document but published on or after the international filing date
 L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 O document referring to an oral disclosure, use, exhibition or other means
 P document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
 Z document member of the same patent family

Date of the actual completion of the international search

5 July 2002

Date of mailing of the international search report

12/07/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
 Fax: (+31-70) 340-3016

Authorized officer

Vernier, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 02/00404

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 389 700 A (FUJI CAPSULE KABUSHIKI KAISHA) 3 October 1990 (1990-10-03) page 3, line 18 - line 45; claims ---	1-19
A	EP 1 064 910 A (PRIMACARE S A) 3 January 2001 (2001-01-03) page 3, line 11 - line 22 page 10, line 13 - line 24; claims 1,4,7,19-21 ---	1-19
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 15, 6 April 2001 (2001-04-06) & JP 2000 342186 A (YUUSU KK), 12 December 2000 (2000-12-12) abstract -----	1-19

INTERNATIONAL SEARCH REPORT

Internat'l Application No

PCT/IB 02/00404

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9406308	A	31-03-1994	CA 2124010 A1	31-03-1994
			EP 0621752 A1	02-11-1994
			FI 942351 A	20-05-1994
			JP 7502187 T	09-03-1995
			MX 9305081 A1	30-06-1994
			NO 941852 A	18-05-1994
			WO 9406308 A1	31-03-1994
			US 5958502 A	28-09-1999
			US 5792505 A	11-08-1998
WO 8503414	A	15-08-1985	CA 1231934 A1	26-01-1988
			EP 0169893 A1	05-02-1986
			JP 61501078 T	29-05-1986
			WO 8503414 A1	15-08-1985
			US 4689235 A	25-08-1987
GB 655592	A	25-07-1951	NONE	
WO 0036931	A	29-06-2000	DE 19956604 A1	02-11-2000
			AU 2095500 A	12-07-2000
			BR 9916315 A	14-08-2001
			CN 1330519 T	09-01-2002
			WO 0036931 A1	29-06-2000
			EP 1139791 A1	10-10-2001
EP 0389700	A	03-10-1990	JP 1193216 A	03-08-1989
			EP 0389700 A1	03-10-1990
EP 1064910	A	03-01-2001	EP 1064910 A1	03-01-2001
			AU 5818700 A	22-01-2001
			WO 0101929 A2	11-01-2001
JP 2000342186	A	12-12-2000	NONE	